

JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(11) Publication number:

09162935 A

(43) Date of publication of application: 20.06.1997

(51) Int. CI

H04L 27/14

(21) Application number:

07335712

(22) Date of filing:

01.12.1995

(54) FREQUENCY OFFSET DETECTION CIRCUIT

(57) Abstract:

PROBLEM TO BE SOLVED: To output a true intermediate frequency even if a bias occurs in the rate of the occurrence of two kinds of symbols (mark and space) in an FSK signal.

SOLUTION: The in-phase component (i) and the quadrature component (q) of a base band signal, which are obtained by gradrature detecting 2 an input signal which is FSK-modulated, are inputted to a rotation angle detection circuit 3 and a rotation direction judgment circuit 4. Then, phase rotation quantity E and the direction B of positive or negative sense are obtained. Reception symbol timing RT generated in a

(71) Applicant: KOKUSAI ELECTRIC CO LTD

(72) Inventor: YAMAGUCHI HIDETO

URABE KENZO

digital phase locked loop 6 is switched 5 so that it becomes output D1 when B is positive, and output D2 when B is negative, it is inputted to rotation angle averaging circuit 7-1 and 7-2. Then, rotation quantity E is sampled at respective timings and the average values are obtained and are added.

СОРУЯЮНТ: (С)1997, ЈРО

